

UNCLASSIFIED

AD 278 423

*Reproduced
by the*

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

62-444

10

Report No. RF-TR-62-1
REVISED

COPY 78

278423

AD No. —
ASTIA FILE COPY

THE EFFECT OF LOW ASPECT RATIO
RECTANGULAR AND DELTA CRUCIFORM FINS
ON THE STABILITY OF BODIES
OF REVOLUTION WITH TANGENT OGIVES
AT SMALL ANGLES OF ATTACK
THROUGH A MACH NUMBER RANGE OF 0 TO 3.5



aomc

U. S. ARMY ORDNANCE MISSILE COMMAND
REDSTONE ARSENAL ALABAMA

278 423

ASTIA
RECEIVED
JUL 30 1962
RECEIVED
TISIA A

DESTRUCTION

Destroy, do not return.

The first edition of this report, dated 22 May 1962, should be removed from the files and replaced by this REVISED edition.

ASTIA AVAILABILITY NOTICE

Qualified requestors may obtain copies of this report from ASTIA.

2 July 1962

Report No. RF-TR-62-1
REVISED

THE EFFECT OF LOW ASPECT RATIO
RECTANGULAR AND DELTA CRUCIFORM FINS
ON THE STABILITY OF BODIES
OF REVOLUTION WITH TANGENT OGIVES
AT SMALL ANGLES OF ATTACK
THROUGH A MACH NUMBER RANGE OF 0 TO 3.5

By
Clark De Jonge

Advanced Systems Laboratory
Future Missile Systems Division
Research and Development Directorate
U. S. Army Ordnance Missile Command
Redstone Arsenal, Alabama

ABSTRACT

are combined

~~This report combines~~ theoretical and experimental data to provide an easy method of estimating the static and dynamic stability of cylindrical bodies with tangent ogives nose shapes in combination with low aspect ratio cruciform fins.

TABLE OF CONTENTS

| | Page |
|---|------|
| INTRODUCTION | 1 |
| METHOD | 1 |
| Dynamic Stability Estimation | 3 |
| Evaluation of Rolling Moment Coefficients | 4 |
| SUMMARY AND CONCLUSIONS | 5 |

LIST OF ILLUSTRATIONS

| Figure | | Page |
|--------|---|------|
| 1 | Body alone normal force coefficient versus Mach number | 7 |
| 2 | Body alone center of pressure versus Mach number | 8 |
| 3 | Body alone normal force coefficient versus Mach number | 9 |
| 4 | Body alone center of pressure versus Mach number | 10 |
| 5 | Body alone normal force coefficient versus Mach number | 11 |
| 6 | Body alone center of pressure versus Mach number | 12 |
| 7 | Lift curve slope of rectangular wing versus Mach number | 13 |
| 8 | Lift curve slope of delta wing versus Mach number | 14 |

LIST OF SYMBOLS

| | |
|-----------------|--|
| a | Local speed of sound, ft/sec |
| AR | Aspect ratio = $\frac{2b}{c}$ for rectangular fin or 4 tan ϵ for delta fin |
| b | Fin semi-span, ft |
| b ₀ | Total span = 2b + d, ft |
| c | Fin root chord, ft |
| C _l | Rolling moment coefficient = $\frac{L'}{q_0 S d}$ |
| C _m | Pitching moment coefficient = $\frac{M}{q_0 S d}$ |
| C _N | Normal force coefficient = $\frac{N}{q_0 S}$ |
| d | Body diameter (ft) = 1 caliber |
| K | Morikawa's interference factor |
| L' | Rolling moment, ft - lb |
| M | Pitching moment, ft - lb |
| M _∞ | Free stream Mach number = $\frac{V_\infty}{a}$ |
| N | Normal force, lb |
| P _∞ | Free stream static pressure, lb/ft ² |
| p | Roll rate, radians/sec |
| q | Pitch rate, radians/sec |
| q ₀ | Dynamic pressure = $\gamma/2 P_\infty M_\infty^2$, lb/ft ² |
| S | Maximum body cross-sectional area = $\frac{\pi}{4} d^2$, ft ² |
| V _∞ | Free stream velocity, ft/sec |
| X _{CP} | Center of pressure position, cal. |
| α | Angle of attack, radians |
| γ | Ratio of specific heats = 1.4 for air |

LIST OF SYMBOLS (Concluded)

| | |
|------------|---|
| δ | Fin cant, radians |
| ϵ | Fin leading edge angle, measured from root chord, degrees |
| λ | Diameter to total span ratio = $\frac{d}{b_0}$ |


SUBSCRIPTS

| | |
|----------|--|
| a | Rate of change with respect to a |
| δ | Rate of change with respect to δ |
| p | Rate of change with respect to p |
| q | Rate of change with respect to q |
| B | Body |
| F | Fins |
| $F + I$ | Fins + Interferences |
| T | Body + Fins + Interference (i. e. total) |

OTHER COEFFICIENTS

| | |
|---|--|
| $C_{mq} = \frac{\partial C_m}{\partial \left(\frac{qd}{2V} \right)}$ | Pitch damping coefficient |
| $C_{lp} = \frac{\partial C_l}{\partial \left(\frac{pd}{2V} \right)}$ | Roll damping coefficient |
| $C_{l\delta} = \frac{\partial C_l}{\partial \delta}$ | Rolling moment effectiveness coefficient |

Typical configuration



10.0 Caliber body

$$AR = \frac{2b}{c} = 1.00$$

$$\lambda = \frac{d}{b_o} = 0.50$$

$$b_o = 2d$$

$$c = d$$

INTRODUCTION

Aerodynamic design of a missile involves the study of many different configurations and small variations thereof to determine optimum design. The purpose of this report is to reduce the time for determining design through the use of parametrically tabulated data.

Aerodynamic coefficients which can be evaluated from this report are: normal force, total configuration center of pressure position, pitch (or yaw) damping, rolling moment, hinge moment, and control force for movable fins with the body of the missile at zero angle of attack.

METHOD

Body alone aerodynamics were obtained from wind tunnel tests of 4.0 caliber tangent ogive-cylinder bodies through the subsonic and transonic range, (Ref. 1), from theory (Ref. 2) and wind tunnel data (Ref. 3) through the supersonic range. The data were in close agreement as can be seen from Figures 1 through 6.

Fin alone lift was obtained from linear theory which is presented in Figures 7 and 8 and the fin center of pressure from References 4 and 5.

Fin-body interference lift was obtained from References 4 and 5 and the center of pressure of the interference for Reference 6.

The value of C_{N_a} for the body-fin combination is:

$$C_{N_a T} = C_{N_a B} + C_{N_a F} + C_{N_a F(B)} + C_{N_a B(F)}$$

where

$$C_{N_a B} = \text{Body alone } C_{N_a}$$

$$C_{N_a F} = \text{Fin alone } C_{N_a}$$

$C_{N_a F(B)}$ = body normal force coefficient carry over onto the fins.

$C_{N_a B(F)}$ = fin normal force coefficient carry over onto the body.

$$C_{N_a F(B)} = C_{N_a F} K_F(B)$$

$$C_{N_a B(F)} = C_{N_a F} K_B(F)$$

where $K_F(B)$ and $K_B(F)$ are Morikawa's interference factors

$$K_F(B) = \lambda = \frac{d}{b_o}$$

$K_B(F)$ = from Refs 4 and 5.

The center of pressure of the body-fin combination is:

$$X_{CP_T} =$$

$$\frac{C_{N_a B} \cdot X_{CP_B} + C_{N_a F} \cdot X_{CP_F} + C_{N_a F(B)} \cdot X_{CP_{F(B)}} + C_{N_a B(F)} \cdot X_{CP_{B(F)}}}{C_{N_a T}}$$

where

$$X_{CP_B} = \text{Body alone } X_{CP}$$

$$X_{CP_F} = \text{Fin alone } X_{CP}$$

$$X_{CP_{F(B)}} = X_{CP} \text{ of interference of the body on the fins}$$

$$X_{CP_{B(F)}} = X_{CP} \text{ of interference of the fins on the body}$$

Interference effects were combined with the fin alone in the following manner:

$$C_{N_a T} = C_{N_a B} + C_{N_a F} + I$$

where

$$C_{N_a F} + I = C_{N_a F}(1 + K_B(F) + K_F(B))$$

$$\text{and } X_{CP_T} = \frac{C_{N_a B} \cdot X_{CP_B} + C_{N_a F} + I \cdot X_{CP_F} + I}{C_{N_a T}}$$

where

$$X_{CP_F + I} = \frac{C_{N_a F} \cdot X_{CP_F} + C_{N_a B(F)} \cdot X_{CP_{B(F)}} + C_{N_a F(B)} \cdot X_{CP_{F(B)}}}{C_{N_a F} + I}$$

or

$$X_{CP_F + I} = \frac{X_{CP_F} + K_{B(F)} \cdot X_{CP_{B(F)}} + K_{F(B)} \cdot X_{CP_{F(B)}}}{K_T}$$

where $K_T = 1 + K_{B(F)} + K_{F(B)}$

Tables I and II contain $C_{N_{\alpha F + I}}$ and $X_{CP_F + I}$ values estimated by the preceding method.

The designer of movable fins used for control is interested in the lift obtainable by deflecting the fins. This lift coefficient has been defined as $C_{N_{\delta}}$ and is not equal to $C_{N_{\alpha F + I}}$. $K_{F(B)} = 0$ for the fins at an angle of attack and the body at zero angle of attack. There would still be a carry over of lift onto the body due to the fin downwash. Therefore $K_{B(F)} \neq 0$

It was assumed that $K_{B(F)\delta} = K_{B(F)\alpha}$

That is, the interference of the fins on the body will be the same whether the fins alone are at an angle of attack or the fins and body are at an angle of attack. Values of $C_{N_{\delta}}$ are given in Tables IV and V.

DYNAMIC STABILITY ESTIMATION

The damping in pitch term, C_{m_q} , is a result of the fins and body experiencing an effective angle of attack change due to pitch angular velocity. This effective angle is proportional to the distance from the center of gravity and pitch rate and indirectly proportional to the free stream velocity. The restoring moment is proportional to the effective angle of attack, the lift at that location, and the distance from the center of gravity. If C_{m_q} is defined as

$$C_{m_q} = \frac{\partial C_m}{\partial \left(\frac{q d}{2V} \right)}$$

$$\text{then } C_{m_q} = -2C_{N_{\alpha B}}(X_{CP_B} - X_{CG})^2 - 2C_{N_{\alpha F + I}}(X_{CG} - X_{CP_F + I})^2$$

if the body lift is situated entirely at the body alone center of pressure position and the fin lift is acting entirely at the fin center of pressure.

This equation was chosen as the simplest method of accurately evaluating C_{m_q} after a thorough literature survey of available theories and comparison with wind tunnel data.

Results from the above equation, when compared with transonic wind tunnel tests of finned bodies similar to those of this study agreed within the accuracy requirements for the experiment.

Values of $C_{N_{\alpha B}}$ and X_{CP_B} are given in Table III, $C_{N_{\alpha F + I}}$ and $X_{CP_{F + I}}$ values are given in Tables I and II from which C_{m_q} can be readily calculated.

EVALUATION OF ROLLING MOMENT COEFFICIENTS

Slender wing theory was used to predict the rolling moment coefficients for both rectangular and delta planforms. This was felt justifiable for two reasons. (1) The fins considered in this study are of low aspect ratio and (2) slender wing theory matched the rolling characteristics obtained from flight test data for missiles which were equipped with low aspect ratio rectangular fins.

Values of $\frac{C_{l_p}}{AR}$ and $\frac{C_{l_\delta}}{AR}$ were taken from Reference 7 for the fins selected in this study. Since the coefficients of Reference 7 were based on total span and wing area including the hypothetical extension through the body, they were multiplied by the necessary factors to base them on body diameter and body cross-sectional area:

$$C_{l_p} = \frac{C_{l_p}}{AR} \times AR \times \frac{S_{fin}}{S_{ref}} \times \left(\frac{b_o}{d}\right)^2$$

$$C_{l_\delta} = \frac{C_{l_\delta}}{AR} \times AR \times \frac{S_{fin}}{S_{ref}} \times \frac{b_o}{d}$$

$$\text{where } AR = \frac{b_o^2}{S_{fin}}$$

and S_{fin} = area of 2 fins + hypothetical extension through the body are the definitions used in Reference 7.

$$\therefore C_{1p} = \frac{C_{1p}}{AR} \times \frac{b_o^2}{S_{fin}} \times \frac{S_{fin}}{S_{ref}} \times \left(\frac{b_o}{d}\right)^2$$

or

$$= \frac{C_{1p}}{AR} \times \frac{4}{\pi} \left(\frac{b_o}{d}\right)^4$$

$$C_{1\delta} = \frac{C_{1\delta}}{AR} \times \frac{4}{\pi} \left(\frac{b_o}{d}\right)^3$$

Values of C_{1p} and $C_{1\delta}$ are given in Table VI and plotted in Figure 15 for purposes of interpolation.

SUMMARY AND CONCLUSIONS

From theoretical considerations it has been determined that, for a constant span, variations in the aspect ratio of rectangular fins have more effect on the total configuration center of pressure position than the same variations in delta fins. The center of pressure position of rectangular finned bodies moved forward more rapidly at high Mach numbers with increasing aspect ratio as indicated in Figures 9 and 12.

Because the center of pressure position for the total configuration moves more rapidly with varying aspect ratio supersonically than subsonically, by the proper selection of fin span and aspect ratio it is possible to control the Static Margin vs. Mach number, where:
Static Margin = $X_{CP_T} - X_{CG}$.

Figures 10, 11, 13 and 14 indicate the effect of fin size and body length on the center of pressure movement with respect to Mach number.

If fins are used for control as well as stability, delta fins will probably be more desirable than rectangular fins because of the smaller fin center of pressure movement. The hinge line can be positioned to give a smaller hinge moment in the case of delta fins of the same area and span as rectangular fins.

These aerodynamic coefficients are assumed to be sufficiently accurate for preliminary missile design purposes.

Linear interpolation can be used for body lengths other than those in Table III and for fins of different aspect ratio than those listed in Table I, II, IV, and V. Coefficients for fins of different spans than those listed in Table I, II, IV, and V can not be linearly interpolated and should be plotted on semilog paper with $C_{N_0 F} + I$, $X_{CP F} + I$. . . on the logarithm axis and λ on the linear axis.




Figure 1. Body alone normal force coefficient versus Mach number.

8 CAL. BODY

REF. 1

2

3




Figure 2. Body alone center of pressure versus Mach number.

12 CAL. BODY

REF. 1
2
3




Figure 3. Body alone normal force coefficient versus Mach number.




Figure 4. Body alone center of pressure versus Mach number.




Figure 5. Body alone normal force coefficient versus Mach number.




Figure 6. Body alone center of pressure versus Mach number.




Figure 7. Lift curve slope of rectangular wing versus Mach number.




Figure 8. Lift curve slope of delta wing versus Mach number.




Figure 9. Effect of fin angle on center of pressure versus Mach number.
Four delta fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 10. Effect of fin size on center of pressure versus Mach number.
Four rectangular fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 11. Effect of body length on center of pressure versus Mach number.
 Four rectangular fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 12. Effect of aspect ratio on center of pressure versus Mach number.
Four rectangular fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 13. Effect of fin size on center of pressure versus Mach number.
Four delta fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 14. Effect of body length on center of pressure versus Mach number.
Four delta fins at the base of afterbody. 4.0 caliber tangent ogive forebody.




Figure 15. Rolling moment coefficients versus diameter to span ratio.

TABLE I
RECTANGULAR FINS

$$\lambda = 0.4$$

| | AR = 0.50 | | AR = 0.75 | | AR = 1.00 | | AR = 1.50 | |
|------------|----------------------|----------------|----------------------|----------------|----------------------|----------------|----------------------|----------------|
| M_∞ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ |
| 0 | 8.48 | 2.54 | 8.09 | 1.63 | 7.79 | 1.19 | 7.07 | .77 |
| .4 | 8.53 | 2.56 | 8.24 | 1.64 | 7.89 | 1.20 | 7.19 | .78 |
| .8 | 8.86 | 2.77 | 9.12 | 1.79 | 8.76 | 1.31 | 8.88 | .84 |
| 1.0 | 9.43 | 3.00 | 9.96 | 2.00 | 9.52 | 1.50 | 10.48 | 1.00 |
| 1.1 | 9.55 | 2.41 | 10.14 | 1.51 | 9.83 | 1.08 | 11.08 | .65 |
| 1.2 | 9.66 | 2.29 | 10.44 | 1.40 | 10.11 | .98 | 11.25 | .58 |
| 1.3 | 9.83 | 2.19 | 10.56 | 1.33 | 10.36 | .91 | 10.29 | .54 |
| 1.5 | 10.28 | 2.05 | 10.86 | 1.22 | 10.33 | .84 | 8.38 | .52 |
| 1.8 | 10.72 | 1.89 | 10.74 | 1.11 | 9.08 | .79 | 6.53 | .52 |
| 2.0 | 11.01 | 1.81 | 10.14 | 1.08 | 8.10 | .78 | 5.61 | .52 |
| 2.5 | 10.62 | 1.66 | 8.26 | 1.04 | 6.45 | .78 | 4.27 | .52 |
| 3.0 | 9.60 | 1.60 | 6.89 | 1.03 | 5.28 | .77 | 3.44 | .52 |
| 3.5 | 8.55 | 1.57 | 5.77 | 1.03 | 4.32 | .77 | 2.90 | .52 |

Note: (1) All fin centers of pressure are measured in calibers from the base of the fin.

(2) $C_{N_{\alpha F+I}}$ is the lift coefficient of two fins.

TABLE I. - Continued

$\lambda = 0.5$

| M_∞ | AR = 0.50 | | AR = 0.75 | | AR = 1.00 | | AR = 1.50 | |
|------------|----------------------|--------------|----------------------|--------------|----------------------|--------------|----------------------|--------------|
| | $C_{N_{\alpha F+I}}$ | $X_{CP F+I}$ | $C_{N_{\alpha F+I}}$ | $X_{CP F+I}$ | $C_{N_{\alpha F+I}}$ | $X_{CP F+I}$ | $C_{N_{\alpha F+I}}$ | $X_{CP F+I}$ |
| 0 | 4.18 | 1.70 | 3.99 | 1.09 | 3.84 | .80 | 3.48 | .51 |
| .4 | 4.22 | 1.71 | 4.08 | 1.10 | 3.90 | .80 | 3.56 | .52 |
| .8 | 4.45 | 1.85 | 4.58 | 1.20 | 4.40 | .88 | 4.46 | .56 |
| 1.0 | 4.81 | 2.00 | 5.08 | 1.33 | 4.86 | 1.00 | 5.35 | .67 |
| 1.1 | 4.87 | 1.57 | 5.17 | .98 | 4.99 | .69 | 5.57 | .42 |
| 1.2 | 4.92 | 1.47 | 5.29 | .90 | 5.09 | .63 | 5.46 | .38 |
| 1.3 | 4.99 | 1.40 | 5.32 | .86 | 5.14 | .59 | 4.80 | .36 |
| 1.5 | 5.19 | 1.32 | 5.39 | .79 | 4.87 | .55 | 3.79 | .36 |
| 1.8 | 5.36 | 1.22 | 5.07 | .74 | 4.14 | .54 | 2.94 | .35 |
| 2.0 | 5.44 | 1.17 | 4.71 | .72 | 3.66 | .53 | 2.54 | .35 |
| 2.5 | 5.00 | 1.10 | 3.75 | .71 | 2.91 | .53 | 1.97 | .35 |
| 3.0 | 4.42 | 1.08 | 3.10 | .70 | 2.40 | .52 | 1.61 | .35 |
| 3.5 | 3.86 | 1.06 | 2.61 | .70 | 1.99 | .52 | 1.37 | .35 |

TABLE I. - Concluded

| $\lambda = 0.6$ | | | | | | | | |
|-----------------|----------------------|----------------|----------------------|----------------|----------------------|----------------|----------------------|----------------|
| AR = 0.50 | | | AR = 0.75 | | AR = 1.00 | | AR = 1.50 | |
| M_∞ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ |
| 0 | 2.04 | 1.13 | 1.94 | .73 | 1.87 | .53 | 1.70 | .34 |
| .4 | 2.06 | 1.14 | 2.00 | .73 | 1.91 | .54 | 1.74 | .35 |
| .8 | 2.22 | 1.24 | 2.28 | .80 | 2.19 | .59 | 2.22 | .38 |
| 1.0 | 2.43 | 1.33 | 2.57 | .89 | 2.46 | .67 | 2.70 | .44 |
| 1.1 | 2.45 | 1.00 | 2.59 | .62 | 2.49 | .44 | 2.67 | .27 |
| 1.2 | 2.47 | .93 | 2.64 | .57 | 2.46 | .41 | 2.43 | .26 |
| 1.3 | 2.50 | .89 | 2.60 | .55 | 2.34 | .40 | 2.13 | .25 |
| 1.5 | 2.57 | .84 | 2.47 | .53 | 2.16 | .38 | 1.70 | .24 |
| 1.8 | 2.52 | .80 | 2.24 | .51 | 1.84 | .37 | 1.34 | .24 |
| 2.0 | 2.48 | .79 | 2.09 | .49 | 1.64 | .36 | 1.16 | .24 |
| 2.5 | 2.21 | .76 | 1.68 | .48 | 1.32 | .36 | .92 | .23 |
| 3.0 | 1.96 | .74 | 1.40 | .47 | 1.11 | .35 | .76 | .23 |
| 3.5 | 1.73 | .72 | 1.19 | .47 | .93 | .35 | .65 | .23 |

TABLE II
DELTA FINS

$$\lambda = 0.4$$

| | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
|------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|
| M_∞ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ |
| .4 | 6.91 | 1.61 | 6.46 | 1.11 | 5.99 | .85 | 5.78 | .69 |
| .8 | 7.82 | 1.55 | 7.50 | 1.06 | 7.22 | .80 | 7.16 | .65 |
| 1.1 | 8.65 | 1.42 | 8.45 | .93 | 8.30 | .69 | 8.00 | .54 |
| 1.2 | 8.54 | 1.42 | 8.34 | .93 | 8.00 | .69 | 7.69 | .54 |
| 1.3 | 8.34 | 1.42 | 8.15 | .93 | 7.73 | .69 | 7.39 | .54 |
| 1.5 | 8.15 | 1.42 | 7.63 | .93 | 7.32 | .69 | 6.85 | .54 |
| 1.8 | 7.86 | 1.42 | 7.34 | .93 | 6.74 | .69 | 6.17 | .54 |
| 2.0 | 7.67 | 1.42 | 7.04 | .93 | 6.38 | .69 | 5.75 | .54 |
| 2.5 | 7.21 | 1.42 | 6.35 | .93 | 5.59 | .69 | 4.69 | .54 |
| 3.0 | 6.91 | 1.42 | 5.77 | .93 | 4.89 | .69 | 3.71 | .54 |
| 3.5 | 6.54 | 1.42 | 5.21 | .93 | 4.03 | .69 | 3.06 | .54 |

TABLE II. - Continued

$$\lambda = 0.5$$

| M_∞ | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
|------------|-----------------------|--------------|-----------------------|--------------|-----------------------|--------------|-----------------------|--------------|
| | $C_{N_\alpha F+I}$ | $X_{CP F+I}$ | $C_{N_\alpha F+I}$ | $X_{CP F+I}$ | $C_{N_\alpha F+I}$ | $X_{CP F+I}$ | $C_{N_\alpha F+I}$ | $X_{CP F+I}$ |
| .4 | 3.35 | 1.07 | 3.13 | .74 | 2.91 | .57 | 2.80 | .46 |
| .8 | 3.76 | 1.04 | 3.62 | .71 | 3.49 | .54 | 3.46 | .43 |
| 1.1 | 4.23 | .95 | 4.02 | .62 | 3.92 | .46 | 3.73 | .36 |
| 1.2 | 4.10 | .95 | 3.91 | .62 | 3.72 | .46 | 3.54 | .36 |
| 1.3 | 3.96 | .95 | 3.80 | .62 | 3.58 | .46 | 3.40 | .36 |
| 1.5 | 3.81 | .95 | 3.62 | .62 | 3.38 | .46 | 3.15 | .36 |
| 1.8 | 3.64 | .95 | 3.36 | .62 | 3.07 | .46 | 2.81 | .36 |
| 2.0 | 3.54 | .95 | 3.24 | .62 | 2.92 | .46 | 2.63 | .36 |
| 2.5 | 3.31 | .95 | 2.91 | .62 | 2.55 | .46 | 2.14 | .36 |
| 3.0 | 3.17 | .95 | 2.64 | .62 | 2.21 | .46 | 1.68 | .36 |
| 3.5 | 2.9 | .95 | 2.38 | .62 | 1.83 | .46 | 1.39 | .36 |

TABLE II. - Concluded

$$\lambda = 0.6$$

| | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
|------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|
| M_∞ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ | $C_{N_{\alpha F+I}}$ | $X_{CP_{F+I}}$ |
| .4 | 1.58 | .71 | 1.48 | .49 | 1.37 | .38 | 1.32 | .31 |
| .8 | 1.80 | .69 | 1.73 | .47 | 1.66 | .36 | 1.65 | .29 |
| 1.1 | 1.94 | .61 | 1.83 | .41 | 1.76 | .30 | 1.67 | .24 |
| 1.2 | 1.86 | .61 | 1.76 | .41 | 1.66 | .30 | 1.58 | .24 |
| 1.3 | 1.79 | .61 | 1.69 | .41 | 1.59 | .30 | 1.51 | .24 |
| 1.5 | 1.71 | .61 | 1.57 | .41 | 1.49 | .30 | 1.40 | .24 |
| 1.8 | 1.62 | .61 | 1.50 | .41 | 1.37 | .30 | 1.25 | .24 |
| 2.0 | 1.57 | .61 | 1.44 | .41 | 1.30 | .30 | 1.19 | .24 |
| 2.5 | 1.47 | .61 | 1.29 | .41 | 1.14 | .30 | .95 | .24 |
| 3.0 | 1.41 | .61 | 1.17 | .41 | 1.00 | .30 | .75 | .24 |
| 3.5 | 1.33 | .61 | 1.06 | .41 | .83 | .30 | .62 | .24 |

TABLE III
BODY ALONE AERODYNAMIC COEFFICIENTS

| | 8* Cal. body | | 10 Cal. body | | 12 Cal. body | | 14 Cal. body | |
|------------|------------------|------------|------------------|------------|------------------|------------|------------------|------------|
| M_∞ | $C_{N_\alpha B}$ | X_{CP_B} | $C_{N_\alpha B}$ | X_{CP_B} | $C_{N_\alpha B}$ | X_{CP_B} | $C_{N_\alpha B}$ | X_{CP_B} |
| 0 | 2.03 | 5.50 | 2.32 | 6.53 | 2.39 | 8.21 | 2.67 | 9.45 |
| .4 | 1.83 | 5.87 | 2.10 | 7.15 | 2.18 | 8.75 | 2.36 | 10.20 |
| .8 | 2.40 | 5.57 | 2.46 | 7.00 | 2.51 | 8.62 | 2.54 | 10.20 |
| 1.0 | 2.75 | 4.95 | 2.80 | 6.45 | 2.88 | 7.83 | 3.15 | 9.18 |
| 1.1 | 2.69 | 5.18 | 2.81 | 6.85 | 2.91 | 8.06 | 3.10 | 9.24 |
| 1.2 | 2.64 | 5.48 | 2.75 | 7.14 | 2.85 | 8.55 | 3.04 | 9.80 |
| 1.3 | 2.62 | 5.65 | 2.72 | 7.31 | 2.80 | 8.88 | 2.99 | 10.40 |
| 1.5 | 2.71 | 5.85 | 2.75 | 7.47 | 2.79 | 9.26 | 2.95 | 10.94 |
| 1.8 | 2.85 | 5.63 | 2.85 | 7.48 | 2.85 | 9.40 | 2.94 | 11.33 |
| 2.0 | 2.90 | 5.44 | 2.92 | 7.39 | 2.94 | 9.30 | 2.97 | 11.35 |
| 2.5 | 3.01 | 5.17 | 3.06 | 7.12 | 3.10 | 9.08 | 3.13 | 11.05 |
| 3.0 | 3.06 | 5.05 | 3.16 | 6.95 | 3.25 | 8.87 | 3.26 | 10.75 |
| 3.5 | 3.05 | 5.01 | 3.20 | 6.82 | 3.30 | 8.70 | 3.35 | 10.60 |

* Includes 4.0 cal. tangent ogive
 X_{CP_B} calibers from the base

TABLE IV
RECTANGULAR FINS

$\lambda = 0.4$

| | AR = 0.50 | | AR = 1.00 | | AR = 0.75 | | AR = 1.50 | |
|------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|----------------|
| M_∞ | $C_{N\delta}$ | $x_{CP\delta}$ | $C_{N\delta}$ | $x_{CP\delta}$ | $C_{N\delta}$ | $x_{CP\delta}$ | $C_{N\delta}$ | $x_{CP\delta}$ |
| 0 | 6.65 | 2.54 | 6.34 | 1.63 | 6.11 | 1.19 | 5.54 | .77 |
| .4 | 6.69 | 2.56 | 6.47 | 1.64 | 6.19 | 1.20 | 5.64 | .78 |
| .8 | 7.00 | 2.77 | 7.21 | 1.79 | 6.93 | 1.31 | 7.02 | .84 |
| 1.0 | 7.51 | 3.00 | 7.93 | 2.00 | 7.40 | 1.50 | 8.34 | 1.00 |
| 1.1 | 7.60 | 2.41 | 8.07 | 1.51 | 7.82 | 1.08 | 8.82 | .65 |
| 1.2 | 7.69 | 2.29 | 8.31 | 1.40 | 8.05 | .98 | 8.95 | .58 |
| 1.3 | 7.82 | 2.19 | 8.40 | 1.33 | 8.25 | .91 | 8.11 | .54 |
| 1.5 | 8.18 | 2.05 | 8.64 | 1.22 | 8.20 | .84 | 6.47 | .52 |
| 1.8 | 8.53 | 1.89 | 8.53 | 1.11 | 7.07 | .79 | 4.93 | .52 |
| 2.0 | 8.76 | 1.81 | 7.97 | 1.08 | 6.24 | .78 | 4.19 | .52 |
| 2.5 | 8.42 | 1.66 | 6.36 | 1.04 | 4.86 | .78 | 3.12 | .52 |
| 3.0 | 7.50 | 1.60 | 5.22 | 1.03 | 3.92 | .77 | 2.49 | .52 |
| 3.5 | 6.60 | 1.57 | 4.32 | 1.03 | 3.16 | .77 | 2.08 | .52 |

- NOTE: (1) All fin centers of pressure are measured in calibers from the base of the fin.
- (2) $C_{N\delta}$ values are for 2 fins deflected through an angle δ of radians.

TABLE IV. - Continued

$$\lambda = 0.5$$

| M_∞ | AR = 0.50 | | AR = 0.75 | | AR = 1.00 | | AR = 1.50 | |
|------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|----------------|
| | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ |
| 0 | 3.16 | 1.70 | 3.02 | 1.09 | 2.90 | .80 | 2.63 | .51 |
| .4 | 3.20 | 1.71 | 3.09 | 1.10 | 2.96 | .80 | 2.70 | .52 |
| .8 | 3.42 | 1.85 | 3.52 | 1.20 | 3.38 | .88 | 3.43 | .56 |
| 1.0 | 3.74 | 2.00 | 3.95 | 1.33 | 3.78 | 1.00 | 4.16 | .67 |
| 1.1 | 3.79 | 1.57 | 4.02 | .98 | 3.88 | .69 | 4.31 | .42 |
| 1.2 | 3.82 | 1.47 | 4.11 | .90 | 3.94 | .63 | 4.18 | .38 |
| 1.3 | 3.88 | 1.40 | 4.12 | .86 | 3.97 | .59 | 3.59 | .36 |
| 1.5 | 4.03 | 1.32 | 4.16 | .79 | 3.69 | .55 | 2.73 | .36 |
| 1.8 | 4.14 | 1.22 | 3.84 | .74 | 3.03 | .54 | 2.05 | .35 |
| 2.0 | 4.19 | 1.17 | 3.51 | .72 | 2.63 | .53 | 1.75 | .35 |
| 2.5 | 3.78 | 1.10 | 2.70 | .71 | 2.03 | .53 | 1.33 | .35 |
| 3.0 | 3.26 | 1.08 | 2.17 | .70 | 1.64 | .52 | 1.08 | .35 |
| 3.5 | 2.78 | 1.06 | 1.80 | .70 | 1.35 | .52 | .91 | .35 |

TABLE IV. - Concluded

$$\lambda = 0.6$$

| M_∞ | AR = 0.50 | | AR = 0.75 | | AR = 1.00 | | AR = 1.50 | |
|------------|---------------|----------------|---------------|----------------|---------------|----------------|---------------|----------------|
| | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ |
| 0 | 1.50 | 1.13 | 1.42 | .73 | 1.37 | .53 | 1.25 | .34 |
| .4 | 1.52 | 1.14 | 1.47 | .73 | 1.41 | .54 | 1.28 | .35 |
| .8 | 1.67 | 1.24 | 1.71 | .80 | 1.65 | .59 | 1.67 | .38 |
| 1.0 | 1.86 | 1.33 | 1.97 | .89 | 1.88 | .67 | 2.07 | .44 |
| 1.1 | 1.87 | 1.00 | 1.95 | .62 | 1.90 | .44 | 2.00 | .27 |
| 1.2 | 1.89 | .93 | 2.01 | .57 | 1.85 | .41 | 1.75 | .26 |
| 1.3 | 1.91 | .89 | 1.96 | .55 | 1.71 | .40 | 1.48 | .25 |
| 1.5 | 1.95 | .84 | 1.81 | .53 | 1.53 | .38 | 1.33 | .24 |
| 1.8 | 1.87 | .80 | 1.58 | .51 | 1.25 | .37 | .86 | .24 |
| 2.0 | 1.81 | .79 | 1.45 | .49 | 1.09 | .36 | .74 | .24 |
| 2.5 | 1.56 | .76 | 1.12 | .48 | .85 | .36 | .58 | .23 |
| 3.0 | 1.34 | .74 | .91 | .47 | .71 | .35 | .48 | .23 |
| 3.5 | 1.15 | .72 | .76 | .47 | .59 | .35 | .41 | .23 |

TABLE V
DELTA FINS

$\lambda = 0.4$

| | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
|------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|
| M_∞ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ |
| .4 | 5.49 | 1.61 | 5.13 | 1.11 | 4.76 | .85 | 4.59 | .69 |
| .8 | 6.22 | 1.55 | 5.96 | 1.06 | 5.74 | .80 | 5.69 | .65 |
| 1.1 | 6.86 | 1.42 | 6.70 | .93 | 6.57 | .69 | 6.32 | .54 |
| 1.2 | 6.77 | 1.42 | 6.60 | .93 | 6.32 | .69 | 6.06 | .54 |
| 1.3 | 6.60 | 1.42 | 6.44 | .93 | 6.09 | .69 | 5.81 | .54 |
| 1.5 | 6.44 | 1.42 | 6.02 | .93 | 5.75 | .69 | 5.36 | .54 |
| 1.8 | 6.20 | 1.42 | 5.77 | .93 | 5.27 | .69 | 4.81 | .54 |
| 2.0 | 6.04 | 1.42 | 5.52 | .93 | 4.98 | .69 | 4.46 | .54 |
| 2.5 | 5.67 | 1.42 | 4.96 | .93 | 4.34 | .69 | 3.61 | .54 |
| 3.0 | 5.42 | 1.42 | 4.49 | .93 | 3.77 | .69 | 2.84 | .54 |
| 3.5 | 5.11 | 1.42 | 4.03 | .93 | 3.09 | .69 | 2.32 | .54 |

TABLE V . Continued

| $\lambda = 0.5$ | | | | | | | | |
|-----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|
| | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
| M_∞ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ |
| .4 | 2.53 | 1.07 | 2.37 | .74 | 2.20 | .57 | 2.12 | .46 |
| .8 | 2.84 | 1.04 | 2.74 | .71 | 2.64 | .54 | 2.62 | .43 |
| 1.1 | 3.24 | .95 | 3.05 | .62 | 2.96 | .46 | 2.80 | .36 |
| 1.2 | 3.12 | .95 | 2.95 | .62 | 2.78 | .46 | 2.64 | .36 |
| 1.3 | 3.00 | .95 | 2.85 | .62 | 2.67 | .46 | 2.54 | .36 |
| 1.5 | 2.86 | .95 | 2.70 | .62 | 2.50 | .46 | 2.32 | .36 |
| 1.8 | 2.72 | .95 | 2.49 | .62 | 2.26 | .46 | 2.05 | .36 |
| 2.0 | 2.64 | .95 | 2.39 | .62 | 2.14 | .46 | 1.91 | .36 |
| 2.5 | 2.45 | .95 | 2.14 | .62 | 1.85 | .46 | 1.54 | .36 |
| 3.0 | 2.34 | .95 | 1.93 | .62 | 1.59 | .46 | 1.20 | .36 |
| 3.5 | 2.13 | .95 | 1.73 | .62 | 1.31 | .46 | .98 | .36 |

TABLE V. - Concluded

| $\lambda = 0.6$ | | | | | | | | |
|-----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|-----------------------|----------------|
| M_∞ | $\epsilon = 10^\circ$ | | $\epsilon = 15^\circ$ | | $\epsilon = 20^\circ$ | | $\epsilon = 25^\circ$ | |
| | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ | $C_{N\delta}$ | $X_{CP\delta}$ |
| .4 | 1.16 | .71 | 1.08 | .49 | 1.00 | .38 | .97 | .31 |
| .8 | 1.32 | .69 | 1.27 | .47 | 1.21 | .36 | 1.21 | .29 |
| 1.1 | 1.41 | .61 | 1.31 | .41 | 1.25 | .30 | 1.17 | .24 |
| 1.2 | 1.34 | .61 | 1.24 | .41 | 1.16 | .30 | 1.10 | .24 |
| 1.3 | 1.27 | .61 | 1.18 | .41 | 1.10 | .30 | 1.04 | .24 |
| 1.5 | 1.20 | .61 | 1.09 | .41 | 1.03 | .30 | .96 | .24 |
| 1.8 | 1.13 | .61 | 1.03 | .41 | .94 | .30 | .85 | .24 |
| 2.0 | 1.09 | .61 | .99 | .41 | .88 | .30 | .81 | .24 |
| 2.5 | 1.01 | .61 | .88 | .41 | .77 | .30 | .63 | .24 |
| 3.0 | .97 | .61 | .79 | .41 | .67 | .30 | .49 | .24 |
| 3.5 | .91 | .61 | .71 | .41 | .55 | .30 | .40 | .24 |

TABLE VI
ROLLING MOMENT COEFFICIENTS

| λ | $C_{l p}$ | $C_{l \delta}^*$ |
|-----------|-----------|------------------|
| .4 | -7.958 | 4.604 |
| .5 | -2.982 | 2.042 |
| .6 | -1.182 | .920 |

Using Reference 7

* $C_{l \delta}$ is for the fins differentially
deflected through δ radians.

REFERENCES

1. Gwin, H. and Spring, D.: "Stability Characteristics of a Family of Tangent Ogive - Cylinder Bodies at Mach Numbers from 0.2 to 1.5" ABMA Rpt. No. RG-TR-61-1, June 1961.
2. Royal Aeronautical Society Data Sheets.
3. Johnson, L. H.: "High Supersonic and Hypersonic Aerodynamic Derivatives" Temco Rpt. No. 00.187, June 1960.
4. Low, L. and Stone, H. N.: "The Subsonic Aerodynamic Characteristics of Wings in Combination with Slender Bodies of Revolution" Cornell Aeronautical Laboratory, Inc. Rpt. No. CAL/CM-679, July 1951.
5. Gafarian, A. V. and Phillips, W. L.: "The Supersonic Lift and Centers of Pressure of Rectangular and Clipped-Delta Fins in Combination with Long Cylindrical Bodies - Comparison Between Theory and Experiment" NOTS TM-966, 1952.
6. Pitts, W. C., Nielsen, J. N., and Kaatari, G. E.: "Lift and Center of Pressure of Wing-Body-Tail Combinations at Subsonic Transonic, and Supersonic Speeds" NACA Report 1307, 1959.
7. Adams, G. J. and Dugan, D. W.: "Theoretical Damping in Roll and Rolling Moment Due to Differential Wing Incidence for Slender Cruciform Wings and Wing-Body Combinations" NACA Rpt. 1088, 1952.

APPROVAL

Report No. RF-TR-62-1

REVISED
2 July 1962

Clark DeJonge
Clark DeJonge, author

David A. Mendel
David A. Mendel
Chief, Aeromechanics Section

Henry A. D. Lavender
Robert E. Lavender
Director, Advanced Systems Laboratory

DISTRIBUTION

| | Copy |
|---|-------|
| In accordance with Lists A, C, and DA of the Guided Missile Technical Information Distribution List, MML 200/23 List No. 23, 3 April 1961 | 1-182 |
| Deputy Chief of Staff for Military Operations Department of the Army Washington 25, D. C. ATTN: Guided Missiles | 183 |
| Chief of Research and Development Office Chief of Staff Department of the Army Washington 25, D. C. | 184 |
| Commanding Officer Office of Ordnance Research Box CM, Duke Station Durham, North Carolina ATTN: ORDOR-PC | 185 |
| Air Force Office of Scientific Research Temporary T Building 14th Street and Constitution Avenue, N. W. Washington 25, D. C. ATTN: SREC | 186 |
| Commanding Officer U. S. Naval Guided Missile School Pomona, California | 187 |
| George C. Marshall Space Flight Center Aeroballistics Division Redstone Arsenal, Alabama ATTN: Mr. Ed Linsley | 188 |

DISTRIBUTION (Concluded)

| | Copy |
|--|---------|
| Commander | |
| Army Ordnance Missile Command | |
| Redstone Arsenal, Alabama | |
| ATTN: ORDXM-W (Historian) | 189 |
| ORDXM-R (Director) | 190 |
| ORDXM-RI (Missile "B" Branch) | 191 |
| ORDXM-RM (Antimissile Missile System Office) | 192 |
| ORDXM-RK (Propulsion Lab) | 193 |
| ORDXM-RG (Guidance, Control and Aeroballistics Lab) | |
| (Dr. McCorkle) | 194 |
| (Mr. Deep) | 195 |
| ORDXM-RR (Research Lab) | 196 |
| ORDXM-RS (Structures and Mechanics Lab) | 197 |
| ORDXM-RH (Surface to Air Missile Systems Office) | 198 |
| ORDXM-RL (Launch and Ancillary Lab) | 199 |
| ORDXM-RT (Test and Evaluation Lab) | 200 |
| ORDXM-RF (Future Missile Systems Division) | 201 |
| ORDXM-RFS (Advanced Systems Lab) | 202-216 |
| ORDXM-RB (Technical Library) | 217-222 |
| ORDXM-RAP (Publication and Information Services Branch) | 223 |

| | | | | |
|---|---|---|---|--|
| AD Army Ordnance Missile Command, Research & Development Directorate, Future Missile Systems Division, Redstone Arsenal, Alabama THE EFFECT OF LOW ASPECT RATIO RECTANGULAR AND DELTA CRUCIFORM FINS ON THE STABILITY OF BODIES OF REVOLUTION WITH TANGENT OGIVES AT SMALL ANGLES OF ATTACK THROUGH A MACH NUMBER RANGE OF 0 TO 3.5 Clark De Jonge | UNCLASSIFIED 1. Cylindrical bodies--Dynamic stability 2. Cylindrical bodies--Static stability 3. Fins--Aspect ratio 4. Ogives--Stability 1. Clark De Jonge | AD Army Ordnance Missile Command, Research & Development Directorate, Future Missile Systems Division, Redstone Arsenal, Alabama THE EFFECT OF LOW ASPECT RATIO RECTANGULAR AND DELTA CRUCIFORM FINS ON THE STABILITY OF BODIES OF REVOLUTION WITH TANGENT OGIVES AT SMALL ANGLES OF ATTACK THROUGH A MACH NUMBER RANGE OF 0 TO 3.5 Clark De Jonge | UNCLASSIFIED 1. Cylindrical bodies--Dynamic stability 2. Cylindrical bodies--Static stability 3. Fins--Aspect ratio 4. Ogives--Stability 1. Clark De Jonge | DISTRIBUTION: Copies obtainable from ASTIA, Arlington Hall Station, Arlington 12, Virginia |
| AOMC RF-TR-62-1, REVISED, 2 Jul 62, 39 pp - illus. Unclassified Report This report combines theoretical and experimental data to provide an easy method of estimating the static and dynamic stability of cylindrical bodies. | | AOMC RF-TR-62-1, REVISED, 2 Jul 62, 39 pp - illus. Unclassified Report This report combines theoretical and experimental data to provide an easy method of estimating the static and dynamic stability of cylindrical bodies. | | |
| AD Army Ordnance Missile Command, Research & Development Directorate, Future Missile Systems Division, Redstone Arsenal, Alabama THE EFFECT OF LOW ASPECT RATIO RECTANGULAR AND DELTA CRUCIFORM FINS ON THE STABILITY OF BODIES OF REVOLUTION WITH TANGENT OGIVES AT SMALL ANGLES OF ATTACK THROUGH A MACH NUMBER RANGE OF 0 TO 3.5 Clark De Jonge | UNCLASSIFIED 1. Cylindrical bodies--Dynamic stability 2. Cylindrical bodies--Static stability 3. Fins--Aspect ratio 4. Ogives--Stability 1. Clark De Jonge | AD Army Ordnance Missile Command, Research & Development Directorate, Future Missile Systems Division, Redstone Arsenal, Alabama THE EFFECT OF LOW ASPECT RATIO RECTANGULAR AND DELTA CRUCIFORM FINS ON THE STABILITY OF BODIES OF REVOLUTION WITH TANGENT OGIVES AT SMALL ANGLES OF ATTACK THROUGH A MACH NUMBER RANGE OF 0 TO 3.5 Clark De Jonge | UNCLASSIFIED 1. Cylindrical bodies--Dynamic stability 2. Cylindrical bodies--Static stability 3. Fins--Aspect ratio 4. Ogives--Stability 1. Clark De Jonge | DISTRIBUTION: Copies obtainable from ASTIA, Arlington Hall Station, Arlington 12, Virginia |
| AOMC RF-TR-62-1, REVISED, 2 Jul 62, 39 pp - illus. Unclassified Report This report combines theoretical and experimental data to provide an easy method of estimating the static and dynamic stability of cylindrical bodies. | | AOMC RF-TR-62-1, REVISED, 2 Jul 62, 39 pp - illus. Unclassified Report This report combines theoretical and experimental data to provide an easy method of estimating the static and dynamic stability of cylindrical bodies. | | |